

橡塑膠, PVC/TPR/EVA類雙腕式高速造粒整廠設備(風冷式)

Rubber,PVC/TPR/EVA double-shaft hi-speed granulator(air cooling)



此機臺用於PVC, EVA, TPR等塑膠原料的生產, 包括主機, 雙腕入料, 模頭切粒等系統將密煉機攪拌好的原料經雙腕擠入造粒機內經螺桿擠出切成粒子, 此機臺操作簡單。

This machine is normally used to produce PVC, EVA and TPR raw material. It consists of main body, -shaft feeder and die-face cutting system etc. Put the mixed material into the feeding inlet. After being pushed in by two shafts, the material is extruded by a screw. The granules which being cut the final product. This machine is easy to operate.

型號	押出產量	螺桿直徑	螺桿	傳動馬力	電熱容量	溫度控制	雙腕入料動力	模頭切粒動力	冷卻系統	震動篩選機	攪拌桶	適合搭配的密煉機
MODEL NO.	EXTRUDING CAPACITY(KG/H)	SCREW DIAMETER	SCREW L/D RATIO	DRIVING MOTOR	HEATER CAPACITY	TEMPERATURE CONTROL(POINTS)	FEEDING MOTOR	CUTTING MOTOR	COOLING SYSTEM	VIBRATOR	MIXER	SUITABLE KNEADER
TG-100	150-200	100MM	12	60HP	////	4段	7.5HP	3HP	5HP	3M	600KG	35LITER 型(MODEL)
TG-120	200-300	120MM	12	75HP	////	4段	10HP	3HP	5HP	3M	600KG	55LITER 型(MODEL)
TG-150	250-400	150MM	12	100HP	////	4段	15HP	3HP	7.5HP	5M	1000KG	75LITER 型(MODEL)

此表僅供參考。 This sheet is only for reference.

